

TEST REPORT

Applicant: Dragino Technology Co., Limited.
Room 202, Block B, BCT Incubation Bases (BaoChengTai),
Address of Applicant: No.8 CaiYunRoad LongCheng Street, LongGang District,
Shenzhen 518116, China

Equipment Under Test (EUT)

Product Name: Temperature & Humidity Sensor
Model No.: LHT65
Trade mark: DRAGINO
Applicable standards: EN 62311:2008
Date of sample receipt: 24 Aug., 2019
Date of Test: 25 Aug., to 08 Oct., 2019
Date of report issue: 09 Oct., 2019
Test Result: PASS*

The CE mark as shown below can be used, under the responsibility of the manufacturer, after completion of an EC Declaration of Conformity and compliance with all relevant EC Directives. The protection requirements with respect to electromagnetic compatibility contained in Directive 1999/5/EC are considered.



Bruce Zhang
Laboratory Manager



This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

| Version No. | Date | Description |
|-------------|---------------|-------------|
| 00 | 09 Oct., 2019 | Original |
| | | |
| | | |
| | | |
| | | |

Tested by:

Carey Chen

Test Engineer

Date:

09 Oct., 2019

Reviewed by:

Winner Zhang

Project Engineer

Date:

09 Oct., 2019

3 Contents

| | Page |
|--|------|
| 1 COVER PAGE..... | 1 |
| 2 VERSION..... | 2 |
| 3 CONTENTS..... | 3 |
| 4 GENERAL INFORMATION | 4 |
| 4.1 CLIENT INFORMATION | 4 |
| 4.2 GENERAL DESCRIPTION OF E.U.T. | 4 |
| 4.3 OPERATING MODES | 4 |
| 4.4 DESCRIPTION OF SUPPORT UNITS..... | 4 |
| 4.5 LABORATORY FACILITY | 4 |
| 4.6 LABORATORY LOCATION | 5 |
| 4.7 TEST INSTRUMENTS LIST..... | 5 |
| 5 TECHNICAL REQUIREMENTS SPECIFICATION IN EN 62311 | 6 |
| 5.1 GENERAL DESCRIPTION OF APPLIED STANDARDS..... | 6 |
| 5.2 RF EXPOSURE EVALUATION..... | 6 |
| 5.2.1 Limit..... | 6 |
| 5.2.2 Test method | 6 |
| 5.2.3 Measurement data: | 7 |
| 5.2.4 Conclusion..... | 7 |

4 General Information

4.1 Client Information

| | |
|-----------------------|--|
| Applicant: | Dragino Technology Co., Limited. |
| Address: | Room 202, Block B, BCT Incubation Bases (BaoChengTai), No.8 CaiYunRoad LongCheng Street, LongGang District, Shenzhen 518116, China |
| Manufacturer/Factory: | Dragino Technology Co., Limited. |
| Address: | Room 202, Block B, BCT Incubation Bases (BaoChengTai), No.8 CaiYunRoad LongCheng Street, LongGang District, Shenzhen 518116, China |

4.2 General Description of E.U.T.

| | |
|-------------------|-------------------------------|
| Product Name: | Temperature & Humidity Sensor |
| Model No.: | LHT65 |
| Hardware version: | LHT65 v1.3 |
| Software version: | LHT65 SW v1.3 |
| Modulation: | LoRa |
| Antenna type: | Internal Antenna |
| Antenna Gain: | 0 dBi |

4.3 Operating Modes

| Operating mode | Detail description |
|-------------------|---|
| Transmitting mode | Keep the TX unit in transmitting mode with modulation |

4.4 Description of Support Units

| |
|-----|
| N/A |
|-----|

4.5 Laboratory Facility

| |
|---|
| <p>The test facility is recognized, certified, or accredited by the following organizations:</p> <ul style="list-style-type: none"> ● FCC - Registration No.: 727551 Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC (Federal Communications Commission). The Registration No. is 727551. ● IC - Registration No.: 10106A-1 The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1. ● CNAS - Registration No.: CNAS L6048 Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048. ● A2LA - Registration No.: 4346.01 This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: https://portal.a2la.org/scopepdf/4346-01.pdf |
|---|

4.6 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.
 Address: No. B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,
 Bao'an District, Shenzhen, Guangdong, China
 Tel: +86-755-23118282
 Fax: +86-755-23116366

4.7 Test Instruments list

| Conducted method: | | | | | |
|-------------------------|--------------|-----------|------------------|----------------------|--------------------------|
| Test Equipment | Manufacturer | Model No. | Serial No. | Cal. Date (mm-dd-yy) | Cal. Due date (mm-dd-yy) |
| Spectrum Analyzer | Agilent | N9020A | MY50510123 | 11-10-2018 | 11-09- 2019 |
| Vector Signal Generator | Agilent | N5182A | MY49060014 | 11-10-2018 | 11-09- 2019 |
| Signal Generator | R&S | SMR20 | 1008100050 | 03-07-2019 | 03-06- 2020 |
| Power Sensor | D.A.R.E | RPR3006W | 15I00041SNO12 | 11-10-2018 | 11-09- 2019 |
| Power Sensor | D.A.R.E | RPR3006W | 15I00041SNO54 | 11-10-2018 | 11-09- 2019 |
| Power Sensor | D.A.R.E | RPR3006W | 17I00015SNO27 | 11-10-2018 | 11-09- 2019 |
| Power Sensor | D.A.R.E | RPR3006W | 17I00015SNO28 | 11-10-2018 | 11-09- 2019 |
| RF Switch Unit | Ascentest | AT890-RFB | N/A | N/A | N/A |
| Test Software | MWRFTTEST | MTS 8310 | Version: 2.0.0.0 | | |

5 Technical Requirements Specification in EN 62311

5.1 General Description of Applied Standards

EN 62311 Generic standard to demonstrate the compliance of electronic and electrical apparatus with the basic restrictions related to human exposure to electromagnetic fields (0 Hz–300 GHz) is to demonstrate the compliance of apparatus with the basic restrictions or reference levels on exposure of the general public related to electric, magnetic, electromagnetic fields as well as induced and contact current.

5.2 RF Exposure Evaluation

5.2.1 Limit

Reference levels for electric, magnetic and electromagnetic fields
(0 Hz to 300 GHz, unperturbed rms values)

| Frequency range | E-field strength (V/m) | H-field strength (A/m) | B-field (μT) | Equivalent plane wave power density S_{eq} (W/m ²) |
|-----------------|------------------------|------------------------|---------------------|--|
| 0-1 Hz | — | $3,2 \times 10^4$ | 4×10^4 | — |
| 1-8 Hz | 10 000 | $3,2 \times 10^4/f^2$ | $4 \times 10^4/f^2$ | — |
| 8-25 Hz | 10 000 | $4\ 000/f$ | $5\ 000/f$ | — |
| 0,025-0,8 kHz | $250/f$ | $4/f$ | $5/f$ | — |
| 0,8-3 kHz | $250/f$ | 5 | 6,25 | — |
| 3-150 kHz | 87 | 5 | 6,25 | — |
| 0,15-1 MHz | 87 | $0,73/f$ | $0,92/f$ | — |
| 1-10 MHz | $87/f^{0,2}$ | $0,73/f$ | $0,92/f$ | — |
| 10-400 MHz | 28 | 0,073 | 0,092 | 2 |
| 400-2 000 MHz | $1,375\ f^{0,2}$ | $0,0037\ f^{0,2}$ | $0,0046\ f^{0,2}$ | $f/200$ |
| 2-300 GHz | 61 | 0,16 | 0,20 | 10 |

Notes:

1. f as indicated in the frequency range column.

5.2.2 Test method

The antenna of the product, under normal use condition is at least 20cm away from the body of the user. Warning statement of the user for keeping 20cm separation distance and the prohibition of operating to a person has been printed on the user manual. So, this product under normal use is located on electromagnetic far field between the human body.

Far Field Calculation Formula

$$E = \frac{\sqrt{30PG(\theta, \phi)}}{r}$$

G = antenna gain relative to an isotropic antenna
 θ, ϕ = elevation and azimuth angles to point of investigation
 r = distance from observation point to the antenna

5.2.3 Measurement data:

| Frequency | Output Power (dBm) | Output Power (mW) | Antenna Gain (dBi) | Antenna Gain (numeric) | E Field Strength (V/m) | E Field Strength Limit (V/m) | Result |
|-----------|--------------------|-------------------|--------------------|------------------------|------------------------|------------------------------|--------|
| 863.1MHz | 12.93 | 19.63 | 0 | 1 | 3.84 | 40.40 | Pass |

5.2.4 Conclusion

Meet the requirements of EN 62311:2008

-----End of report-----